

List of Tables

Tables	Pages	
2.1	Summary of material waste streams	13
3.1	Material shortlist summary table	46
3.2	Reaction rates of MDI with water	80
3.3	Reaction rates of water with MDI binder	82
3.4	A typical table of design of experiments	94
3.5	Table of extruder variables	94
4.1	Shows non-acoustic properties of three extruded samples	100
4.2	Normalised traffic noise spectrum	116
4.3	A summary of the averaged characteristics of the investigated porous materials	146
4.4	Equipment and sample preparation procedures	147
4.5	Summary of the acoustic stimuli and the hardware used in the round-robin experiments	152
5.1	Calibration data for the binder	163
5.2	Shows the calibration data for the car dashboard crumb	164
5.3	Calibration data for the water pump	165
5.4	Calibration data for the hopper	166
5.5	Calibration data for the tyre shred residue	167
5.6	Default values of controlled factors for the prototype extruder	169

5.7	Prototype extruder variables that were changed	170
5.8	Results for extruder variables	171
5.9	Influence of binder (XP2261)	172
5.10	Acoustic and other characteristic data for the extruded materials	184
6.1	Summary of two models to predict the acoustic performance	201
6.2	Summary of the parameters used in Pade approximation for 10% binder	203
6.3	Summary of the parameters used in Pade approximation for 20% binder	204
6.4	Summary of the parameters used in Pade approximation for 30% binder	205
6.5	Summary of the parameters used in Pade approximation for 40% binder	206
6.6	Summary of the parameters used in Pade approximation for 50% binder	207
6.7	Summary of the parameters used in the Johnson-Champoux-Allard model for 10% binder	208
6.8	Summary of the parameters used in the Johnson-Champoux-Allard model for 20% binder	209
6.9	Summary of the parameters used in the Johnson-Champoux-Allard model for 30% binder	210

6.10	Summary of the parameters used in the Johnson- Champoux-Allard model for 40% binder	211
6.11	Summary of the parameters used in the Johnson- Champoux-Allard model for 50% binder	212
7.1	Typical binder formulations for different material densities	216
7.2	Binder properties	218
7.3	Formulation for a product with good absorption and thermal and impact properties	220
7.4	Formulation for a product with good absorption Properties	221
7.5	Formulation for a product with good absorption and thermal properties	222
7.6	Formulation for a product with good absorption and thermal properties	223
7.7	Formulation for a product with good impact properties	224
7.8	Formulation for a product with good absorption	226
7.9	Shows influence of binder on thermal conductivity of dashboard crumb	228
7.10	Formulation for the initial trial	229
7.11	Shows the formulation for the second trial	230

7.12	A summary of the cost analysis model developed for sustainable materials	236
8.1	Shows the formulation for a low density product with good thermal conductivity value	240