

Contents

Abstract	i
Contents	ii
Table of Figures	vii
Acknowledgements	xii
1. Introduction to the project	1
1.1 Problem Description	1
1.2 Aim of the project	5
1.3 Aims and Objectives	5
1.4 Plan of this thesis	6
1.5 Summary of the chapter	8
2. Literature Review	9
2.1 Cold chain Processes	9
2.2 Background to cold chain industry	10
2.3 Importance of temperature control and specific temperature ranges	11
2.4 Frequency of Vaccine wastage	13
2.5 Importance of thermal stability of vaccines	13

2.6	Temperature control of these products	15
2.7	Modelling heat transfer	15
2.8	Summary	31
3.	Theory of Heat Transfer	34
3.1	Modes of Heat Transfer	34
3.1.1	Conduction	35
3.1.2	Convection	43
3.1.3	Radiation	50
3.2	Lumped System Analysis	52
3.3	Summary of the chapter	55
4.	Experimentation and Analysis	56
4.1	Equipment	56
4.1.1	Environmental test chamber	57
4.1.2	Programming Controller	59
4.1.3	Eltek Squirrel data logging equipment	68
4.1.4	Thermistor probes	72
4.1.5	Insulative containers and spacers	72
4.1.6	Phase Change Materials	73
4.2	Experimental Method	75
4.2.1	Experimental tests to see effect of three key parameters on product performance	75

4.2.1.1	Planning the experimental tests to be conducted	76
4.2.1.2	Description of experimental tests	78
4.2.1.3	Execution of experimental tests	80
4.2.2	Experimental tests for size and ambient environment validation	84
4.2.2.1	Description of experimental tests	84
4.2.2.2	Execution of experimental tests	87
4.3	Presentation and Interpretation of results	89
4.3.1	Results showing effect of key parameters on product performance	89
4.3.1.1	Product set of tests	89
4.3.1.2	Chilled PCM set of tests	92
4.3.1.3	Frozen PCM set of tests	95
4.3.2	Results for tests done towards size validation	98
4.4	Summary	100
5.	Model Design and Development	102
5.1	Introduction to spreadsheets	102
5.2	Defining the Physical Model	104
5.3	Defining the Mathematical model	106
5.4	Spreadsheet Layout	109
5.5	Assumptions	114
5.6	Governing Heat Transfer Processes	117

5.7	Model Predicted Results	130
5.7.1	Model predicted results showing the effect of key parameters on product performance	130
5.7.1.1	Product set	130
5.7.1.2	Chilled PCM set	133
5.7.1.3	Frozen PCM set	134
5.7.2	Model predicted results for size and ambient environment validation tests	136
5.8	Summary	139
6.	Analysis of Results and Discussion	140
6.1	Model Validation	140
6.1.1	Comparison for the key parameters	140
	a) Product set of tests	140
	b) Chilled PCM set of tests	145
	c) Frozen PCM set of tests	150
6.1.2	Size and Ambient validation comparisons	155
6.2	Further Results Interpretation	160
6.3	Significance of Work	162
6.4	Summary	163
7.	Summary, Conclusions and Recommendations for further work	165
7.1	Thesis Summary	165
7.2	Key Conclusions	167

7.3	Recommendations for further work	168
8.	References	170
9.	Bibliography	184

Table of Figures

2.1	Axisymmetric finite element mesh used in the simulations	21
3.1	A homogenous slab and variation of temperature	37
3.2	A homogenous slab experiencing a transient in temperature distribution	39
3.3	Figure showing variation of thermal conductivity of some solids with temperature	41
3.4	Figure showing specific heat capacity of a block	42
3.5	Figure showing flow of air past a sharp edge plate	43
3.6	Figure showing plots u Vs t for the three regions formed as a result of fluid flow past sharp edged plate	44
4.1	Figure showing an environmental test chamber	57
4.2	Figure showing air flow in the used environmental test chamber	58
4.3	Figure showing Eurotherm 2404 controller	60
4.4	Figure showing profiles in an SPE	63
4.5	Figure showing screenshot of OPC scope being used as a trend display	64
4.6	Screenshot of chart control panel window	64
4.7	Screenshot of options window	65
4.8	Screenshot of itools view runner used for monitoring a process	66
4.9	Figure showing screenshot of an order code wizard	67

4.10	Figure showing location of available tool bars	68
4.11	Eltek 1000 squirrel data logging equipment	69
4.12	Options available of connecting to the squirrel	70
4.13	Eltek DARCA plus software	71
4.14	Section view of a packaging system	74
4.15	A map of experimental tests to be carried out towards seeing the effect of key parameters on product performance	77
4.16	Figure showing the general packing configuration	78
4.17	Figure showing the carton used in the test	79
4.18	Ambient profile to be used whilst carrying out the experimental tests	82
4.19	Sealed boxes in an environmental test chamber just before the start of a test	83
4.20	Front view of the EPS 70 shipper showing the packing configuration	85
4.21	Isometric view of only the internal components used in the DGP Pallet shipper	86
4.22	Ambient profile to be used when running the test involving the EPS 70 shipper	88
4.23	Ambient profile to be used when running the test involving the DGP Pallet shipper	88
4.24	Figure showing the results from the -1 configuration of the set of tests varying the mass of the product	90
4.25	Figure showing the results from the 0 configuration of the set of tests varying the mass of the product	90
4.26	Figure showing the results from the +1 configuration of the set of tests varying the mass of the product	91

4.27	Figure showing the results from the –1 configuration of the set of tests varying the mass of the chilled PCM	92
4.28	Figure showing the results from the 0 configuration of the set of tests varying the mass of the chilled PCM	93
4.29	Figure showing the results from the +1 configuration of the set of tests varying the mass of the chilled PCM	93
4.30	Figure showing the results from the –1 configuration of the set of tests varying the mass of the frozen PCM	95
4.31	Figure showing the results from the 0 configuration of the set of tests varying the mass of the frozen PCM	96
4.32	Figure showing the results from the +1 configuration of the set of tests varying the mass of the frozen PCM	96
4.33	Figure showing the results from the test carried out in the EPS 70 shipper	98
4.34	Figure showing the results from the test carried out in the EPS Pallet shipper	99
5.1	Figure showing the identified physical model	106
5.2	Figure showing the division of zones within the predictive model	107
5.3	A container with two internal zones	112
5.4	Figure showing how the heat transfer occurs within the quarter volume	119
5.5	Screenshot of data entry work sheet within the predictive model	127
5.6	Figure showing an example of a drop-down menu in the data entry section of the worksheet	128
5.7	Screenshot showing the predicted results section of the Worksheet	129
5.8	Figure showing the results predicted for the –1 configuration of the set of tests varying the mass of the product	131

5.9	Figure showing the results predicted for the 0 configuration of the set of tests varying the mass of the product	132
5.10	Figure showing the results predicted for the +1 configuration of the set of tests varying the mass of the product	132
5.11	Figure showing the results predicted for the –1 configuration of the set of tests varying the mass of the chilled PCM	133
5.12	Figure showing the results predicted for the 0 configuration of the set of tests varying the mass of the chilled PCM	133
5.13	Figure showing the results predicted for the +1 configuration of the set of tests varying the mass of the chilled PCM	134
5.14	Figure showing the results predicted for the –1 configuration of the set of tests varying the mass of the frozen PCM	135
5.15	Figure showing the results predicted for the 0 configuration of the set of tests varying the mass of the frozen PCM	135
5.16	Figure showing the results predicted for the +1 configuration of the set of tests varying the mass of the frozen PCM	136
5.17	Section view showing packing configuration used in EPS 70 shipper	137
5.18	Figure showing the predicted results from the test carried out in the EPS 70 shipper	137
5.19	Figure showing the predicted results from the test carried out in the DGP Pallet shipper	138
6.1	Results comparison between experimental and model predicted for the –1 configuration of the set of tests varying the mass of the product	141
6.2	Results comparison between experimental and model predicted for the 0 configuration of the set of tests varying the mass of the product	142

6.3	Results comparison between experimental and model predicted for the +1 configuration of the set of tests varying the mass of the product	143
6.4	Results comparison between experimental and model predicted for the -1 configuration of the set of tests varying the mass of chilled PCM	146
6.5	Results comparison between experimental and model predicted for the 0 configuration of the set of tests varying the mass of chilled PCM	147
6.6	Results comparison between experimental and model predicted for the +1 configuration of the set of tests varying the mass of chilled PCM	148
6.7	Results comparison between experimental and model predicted for the -1 configuration of the set of tests varying the mass of frozen PCM	151
6.8	Results comparison between experimental and model predicted for the 0 configuration of the set of tests varying the mass of frozen PCM	152
6.9	Results comparison between experimental and model predicted for the +1 configuration of the set of tests varying the mass of frozen PCM	153
6.10	Results comparison between experimental and model predicted for the test carried out in EPS 70 shipper	156
6.11	Results comparison between experimental and model predicted for the test carried out in DGP Pallet shipper	158

Acknowledgements

I would like to acknowledge the input provided by DGP Group Ltd.'s Technology Development & Test Centre and their involvement in knowledge transfer partnership scheme, around which this project is based.

In particular, Dr Alex Roskoss, my industrial supervisor; David Walsh, CEO, DGP Group Ltd. and Dr Alan Foster, a colleague at University of Bristol who provided valuable support and suggestions towards this work.

I would also like to express my thanks to Professor Alastair S Wood and Dr Pete Olley at University of Bradford for providing regular feedback and assistance throughout this project.

Finally, I would like to thank Mike Willis at Momenta for support with the general management of this project.